



#### **AOLAI RESCUE TECHNOLOGY CO.,LTD**

奥来救援科技有限公司

No.1078 Chongde Fifth Avenue, Economic and Technological Development Zone, Dezhou City, Shandong Province


TEL:400 0369 119

www.aolairescue.com



**WWW.AOLAIRESCUE.** 

聚焦应急·专注救援



#### 企业简介 COMPANY PROFILE

Aolai Rescue Technology Co., Ltd., founded in 2009, is a leading privately owned supplier of rescue equipment. The headquarter is located in Dezhou of Shandong province with convenient transportation. Focused on investment, production and best service of emergency rescue equipment, Aolai dedicates to providing innovative hydraulic equipment for rescue, industrial and special tactics applications worldwide. After the establishment, Aolai Rescue has been granted "China National High-Tech Industrial Enterprise", "JMRH Enterprise" and other honors.





WWW.AOLAIRESCUE.COM

Rescue Simulation >>>

www.aolairescue.com

Aolai has "Provincial Engineering Laboratory", , . Aolai Rescue is the Shandong Provincial National Economic Mobilization Center, Engineering Technology Research Center of Dezhou and the member of China Fire Protection Association.

300,000,000 Annual Output Value is nearly 300 million RMB. Sold to more than 40 countries. 2009

Developed more than 120 new products.

Applied for more than 50 patents in recent years.

#### 企业发展 DEVELOPMENT

Aolai Rescue has a professional R&D team and actively cooperates with the Institute of High Energy Physics of the Chinese Academy of Sciences, the Chongging Research Institute of China Coal Science and Industry Group, Shandong University and other university research institutes to carry out industry-university-research cooperation. Aolai has jointly built an ultra-high-pressure hydraulic laboratory and a fire-fighting robot laboratory with Shandong University to achieve resource sharing, project cooperation and personnel training, laying a solid foundation for joint research on ultra-high-pressure hydraulic rescue equipment and fire-fighting robots. In recent years, Aolai has applied for more than 50 patents and developed more than 120 new products.

Sold in more than 40 countries around the world, Aolai rescue products have been tested in the Wenchuan earthquake rescue before the company was established, and played an important role in the Yushu earthquake rescue in Qinghai and the 4.25 Nepal earthquake rescue.


#### 主导产品 L FADING PRODUCTS

Aolai Rescue's leading products cover nearly 100 categories including detection instruments, small fire stations, vehicle modifications, robots, hose accessories, mobile rescue tools, track rescue tools, Shoring system, demolition tools, and agency products. Aolai is currently a manufacturer with the highest industrial concentration and the most abundant product lines in the same industry in China. At present, the demolition series products rank first in the country and are always at the leading level among the peers. The company's annual output value is nearly 300 million yuan.



# **GYJK-F2**

### **Hydraulic Combi Tool**



#### Brief Introduction

液压剪扩器简介

Hydraulic Combi Tool connects to a motor or hand pump through a quick coupler to cut, spread, squeeze and pull. The hydraulic force pushes the piston, which is converted into the force of the tool through the connecting rod. The hand valve controls the opening and closing of the tool. When the hand valve is in the neutral position, the tool does not move and the oil return to the pump.

### Technical Parameter 技术参数

01/Working pressure	72MPa(720bar)
02/Opening distance	330mm
03/Spreading force	53kN
04/Max. cutting capacity (Q235 material)	$\phi 36mm$ (round steel)
	φ20mm(steel plate)
05/Max. spreading distance	405mm
06/Dimensions (L*W*H)	880*255*187mm
07/Weight	15.9kg(With expansion head)

AOLAI-RESCUE | 奥来产品

# **GYJQ-E**Hydraulic Cutter

Aolai hydraulic cutter is specially designed to cut round bar, steel plate and cable.







Round ba





01/Rated working pressure	72MPa(720bar)
02/Max. opening distance at the blade tips	309mm
03/Max. cutting capacity (Q235 material)	φ35mm(round steel) φ25mm(steel plate)
04/Weight	14.9Kg
05/Applicable temperature	-30°C-55°C
06/ Dimensions (L*W*H)	845*255*185mm

#### **Brief Introduction**


液压剪切器简介

Hydraulic cutter works with a motor or hand pump through a quick coupler. The hydraulic force pushes the piston, which is converted into the force of the tool through the connecting rod, thereby cutting objects. The hand valve controls the opening and closing of the tool. When the hand valve is in the neutral position, the tool does not move and the oil return to the pump.

Hydraulic Cutters are specially designed to cut round bar, steel plate and cable. It cuts metal or non-metal structures, rescuing victims trapped in dangerous situations.

#### www.aolairescue.com

PAGE-005



#### ■ Main Features

王安符点

**01**/Hydraulic Cutter connects a hydraulic motor pump or a hydraulic hand pump to cut.

**02**/The main part is made of high-strength alloy. The key seals are imported. The blades are made of imported steel material, having high cutting forces.

**03**/The tool's body is made of aerometal and the surface is ceramicized

**04**/The unique two-way self-locking and automatic-resetting integrated reversing hand valve is convenient for both hands.

**05**/The opening distance at the tip is large, which suitable for most rescue scenes.

06/Seals are all imported from Europe and the United States, with better quality better reliability;

• 04-

The main part is made of high-strength alloy. The key seals are imported. The blades are made of imported steel

**07**/No pigtail hose, easy to carry, store and operate.

**08**/LED lighting at the handle facilitates rescue operation in dimly lit environments.

**09**/The integrated design of handle and switch greatly facilitates the operation of rescue personnel.

# **GYKZ-40P**Hydraulic Spreader

Hydraulic spreaders expand, pry open, support, separate, clamp and pull various material objects.





技术参数



Sprea



Pry opei



Separate




01/Rated working pressure	72MPa
02/Max. spreading distance	752mm
03/Max. pulling force	65kN
04/Weight	14.7kg
05/Dimensions(L*W*H)	812*280*192mm
06/Operating temperature	-30°C-+55°C




It is suitable for fire extinguishing, earthquakes, road traffic accidents and other sudden disasters. The coupler can be plugged and unplugged under pressure. Light weight, high efficiency, compact structure, high power, long life and easy maintenance. The sealing ring has high reliability, long service life and easy maintenance with patent.

www.aolairescue.com PAGE-007







#### Main Features

主要特点

- **01**/ The hand valve is made of new materials, which makes the rescue operation more convenient and safer.
- **02**/No pigtail hose, easy to carry, store and operate.
- **03**/Made of high-strength alloy steel, lightweight but strong spreading force.
- **04**/The handle is convenient for both hands, and the moving parts are equipped with protective covers to protect operator.
- **05**/LED lighting at the handle facilitates rescue operation in dimly lit environments.

AOLAI-RESCUE | 奥来产品











### **Technical Parameter** 技术参数

01/Rated working pressure	72MPa (720bar)
02/Max. Pushing force	99.82kN
03/Closed length	564mm
04/Piston stroke	410mm
05/Extended length	974mm
06/Weight	10.7kg
07/ Dimensions	564*93*332mm
08/Applicable temperature	-30°C-+55°C

#### Hydraulic Ram 液压撑顶器

The Hydraulic Ram is driven by high-pressure hydraulic oil to move the piston and provide powerful force. Hydraulic Ram connects a hydraulic motor pump or a hydraulic hand pump to support, pull, and keep heavy objects stable. Hydraulic Ram can be used to rescue trapped persons in accidents on roads, tracks, airports and buildings.

#### www.aolairescue.com

PAGE-009

## **WN-4**

## Hydraulic Universal Compatible Coupling Converter

• 01\_



Single interface design, can operate under pressure;

Tubing



• 04\_

Female-male couplers, double-tube flat couplers, double-tube single couplers and single-tube single couplers, suitable for most domestic and imported products;

• 05\_

The Interface Adapter is made of high-strength aluminum alloy, is lightweight, and has an interface type that can be quickly connected;

### Hydraulic Universal Compatible Coupling Converter

and tools

This product achieves

interface power sources

perfect matching of

different hydraulic

液压接口转换插排

Ultra-high-pressure hydraulic quick-change interface conversion strip, interface adapter, is a common rescue product. It is mainly used for oil circuit conversion between different rescue products and power sources during the rescue process, ensuring that rescue products with different hydraulic interfaces are compatible with The matching of power sources improves rescue efficiency.

■ Technical Parameter 技术参数

01/ Rated working pressure	72MPa
02/Low pressure oil line overflow	pressure 5MPa
03/Applicable temperature	-30°C-+55°C
04/Weight	9.56kg (Equipped with handle and shock-absorbing)
<b>05/</b> Dimensions(L*W*H)	403*360*150mm

#### www.aolairescue.com

PAGE-019

# HYDRAULIC JACK

### **Hydraulic Jack**

Hydraulic jacks are used with Aolai hydraulic hand pumps and are composed of three specifications. They are used to support heavy objects in accidents, thereby rescuing **Technical** Parameter victims trapped in dangerous environments;







01/ Max. supporting force	10t Operated by hand pump	
02/Closed height	109/129/169/249mm	
03/Stroke	24/44/84/164mm	
04/Max. extended height	133/173/253/413mm	
05/weight	1.6kg/1.8kg/2.1kg/2.7kg	





Hydraulic jacks are used with hydraulic hand pumps and are available in various specifications. It support heavy objects in accidents to rescue victims trapped in dangerous environments. The jack is supplied with oil by a hydraulic hand pump. Under the action of hydraulic pressure, the piston rod extends to lift the weight being supported to a certain height to increase the working space and facilitate the rescue of the victim.

A hydraulic hand pump is used to supply oil. Under the action of hydraulic pressure, the piston rod extends to lift the supported weight to a certain height to increase the working space and facilitate the rescue of the trapped persons; The oil cylinder is made of high strength and lightweight alloy and equipped with a special metal base. The seals are all imported from Germany with better quality.



• 02\_

All seals are imported, with reliable sealing and stable quality.

03\_

Equipped with a special metal anti-slip base, the lifting process is stable;

• 01\_

The cylinder is made of high-strength lightweight alloy, resistant to high pressure and lightweight in structure;





Main Features 主要特点

- 01/The cylinder is made of high-strength lightweight alloy, resistant to high pressure and lightweight in structure;
- 02/All seals are imported, with reliable sealing and stable quality.
- 03/Equipped with a special metal and-sup base, the fitting process is stable;



## **GYKZD-40P**

Battery Spreader

No external oil pipe, easy to

Made of high-strength lightweight alloy steel, light weight and large spreading force

Two-way hydraulic lock and automatic reset control valve can self-lock, with high operating safety

operate, carry and store

#### Battery Spreader

• 03\_

电动扩张器

Battery Spreader is used to spread, pry open, support heavy objects, separate and clamp, and pull objects of various materials. It is suitable for fire extinguishing, earthquakes, road traffic accidents and other sudden disasters. Light weight, high efficiency, compact structure, high power, long life and easy maintenance. The world's top sealing ring brand and patented sealing structure have high reliability, long service life and easy maintenance.

#### Technical Parameter

•04\_

01/ Max.working pressure	720 bar / 72 MPa
02/ Expanding tension force	65KN
03/ Maximum opening distance of b	plade end 750mm
04/ Pulling distance	605mm
05/ Battery capacity	24V 5AH
06/ Weight	20 kg(Without battery)
07/ Dimensions (L x W x H)	920x 275x 298 mm

# **GYJKD-A1**Battery Combi Tool

The Battery Combi Tool mainly cuts plates or round steel and can spread, pull and squeeze, etc.







Spread









**Cut round bar** 

01/ Rated working pressure	72MPa (720bar)
02/Expansion distance	355mm
03/ Maximum expansion tension	58kN
04/Shearing capacity	Ф32mm (round steel)
05/Maximum shear opening	260mm
06/Maximum expansion opening	373mm
07/ Weight	18.5kg (without battery)
08/Traction distance	265mm
<b>19</b> / Dimensions (I *W*H)	927*258*283mm



Since it does not require an external power supply, it is also the first choice rescue product for rescue teams, police, civil defense and other emergencies. This product can be used to demolish metal or non-metal structures. It can cut hinges, door beams, roof beams and other structures after traffic accidents to rescue the injured.

It can be used to shear, expand and move the object of operation. In any case, the object to be operated must be sufficiently supported to prevent danger caused by collapse, etc. When using it, note that only the force arm can work underwater. Do not place the electric combi tool in a wet environment when storing.



#### Main Features

主要特点

- **01**/Configure lights to provide lighting, Night work below;
- **02**/LED indicator show the dump energy of battery, avoiding insufficient power, affecting rescue.
- **03**/Ergonomic carrying handle makes the operation more convenient and precise.
- 04/Using high capacity battery, long relay time.

- **05**/One key switch, instant start.
- **06**/Multiple circuit and mechanical protection measures, securing the product and operator;
- **07**/The blades made of high-strength materials are very durable.
- **08**/The machine serves several purposes, with shear, expansion, traction, extrusion a variety of functions.

AOLAI-RESCUE | 奥来产品

# **GYJQD-A1**

### **Battery Cutter**

Battery Cutters is a special battery-hydraulic cutter toll. No external power source, compact and convenient to use.











Break the metal


01/ Max.working pressure	720 bar / 72 MPa
02/Max.blade opening distance	259 mm
$03/_{Cutting}$ capacity (Q235 Round bar $\phi$ ):	32 mm
<b>04/</b> Weight(w/battery)	17.71kg (without battery)
05/Dimensions (L x W x H)	905 x 257x 285mm



#### Battery Cutter 电动剪切器

Battery cutters is the preferred rescue product for rescue teams, police and civil defense teams. It's used for breaking metal or non-metal structure, widely used in a variety of accident traffic accidents, earthquake, building collapse and other disaster rescue.





#### **Main Features**

主要特点

- **01**/Using high capacity battery, long relay time
- 02/Lamp at handle facilitates night work.
- **03**/The main components are aviation aluminum alloy, with high strength and light weight
- **04**/The product has the function of power display,the power level is displayed in grades. Green color above 20%, red color below 20%.
- **05**/Multiple circuit and mechanical protection measures to ensure the safety of tools and operators;



# **BS-H**Hydraulic Hand Pump



**50**%

Firmness and service life are more than 50% of similar products.

#### Brief Introduction

液压手动泵简介

Hydraulic hand pump is a special rescue device. Provide power for the rescue product, let the rescue product work normally in the event of an accident.Rescue the victims trapped in dangerous environment.

One key switch, instant start.



#### ■ Main Features

主要特点

01/ Equipped with high strength aluminum alloy cylinder and bolt in center. Exceed similar products more than 50% in firmness and service life.

02/ The seals are all imported from foreign countries, with better quality better reliability;

03/ Small size, light weight, easy to carry and no fuel oil.

04/ Simple operation, exert the pressure when open the valve, no complex operation

05/ Large hydraulic oil tank capacity. The oil label is convenient to check, effectively avoid the lack of oil due and make it used normally.

**06/** The function of high and low pressure automatic conversion, improve work efficiency, shorten the rescue time and reduce the physical consumption of rescue personnel.



#### Technical Parameter

BS-H技术参数

Hydraulic fluid


Degree of rigidity

01/ Output pressure	72MPa
02/ Weight	7.38kg (With hydraulic oil, full of oil)

#### Technical Parameter

BS-H2技术参数

01/ Output pressure	72MPa
02/ Weight	6.81 kg(With hydraulic oil, full of oil)
	ú.





www.aolairescue.com PAGE-033

#### Technical Parameter

BS-F技术参数

01/ Output pressure	72MPa
02/ High pressure output flow	1.5mL/per time
03/ Low pressure output flow	30mL/pertime
04/ Volume of hydraulic oil tank	1.5L
05/ Weight	6.7kg



**02**-Handle is convenient for left and right hand operation;



With LED lighting, can be

case of dim light.

accurately operated in the

Zero emission, low noise, energy saving and environmental;

### Introduction of the Battery Hydraulic Pump

电动液压泵简介

Battery hydraulic pump is mainly to provide power for the product work, with light weight, large force, high efficiency. The electric hydraulic pump use the hydraulic power source to dismantle it with other products in the components.

01/ No oil pipe, easy operation, easy carrying and storage

02/ Handle is convenient for left and right hand operation;

**03/** One key switch, instant start.

**04/** With LED lighting, can be accurately operated in the case of dim light.

**05/** Zero emission, low noise, energy saving and environmental;

#### Technical Parameter

技术参数

01 / Weight	9.9kg
<b>02</b> /Rated working pressure	72MPa
<b>03</b> /High pressure flow	0.6L/min
<b>04</b> /Low pressure flow	2.2L/min
<b>05</b> /Battery capacity	45Wh
<b>06</b> /Working hours	60min
07 /Volume of hydraulic oil tank	1.5L
08 /Power	800W

## BJQ-F Motor Pump

#### **8** Te

#### Technical Parameter

技术参数

**72**Rated output pressure

01/ Oil pump type / output type	Dual stage plunger/dual output pump
02/ Rated output pressure	72MPa (720bar)
03/ Rated working speed	$3200\pm200\mathrm{rpm}$
04/ Power	2.6kW
05/ Weight	23.5kg
06/ Hydraulic oil capacity	3.5L

3.5L

Doubled flow function. Two pumps output hydraulic oil at the same time in normal operation. At rated working pressure of 72MPa the flow rate is 0.70 L/min. When the low pressure working pressure is 5MPa, the output flow rate of each channel is 2.85L/min. When the flow doubling function is opened, according to the spin the pointing of the button, the original 2 output combined into the only 1 output of the machine, rated working pressure 72MPa, the output flow rate is 1.35 L/min, Low-pressure work pressure of the 5MPa, the output flow rate is 5.60 L/min.

#### Introduction of Double Speed Output Motor Pump

倍速式双输出机动泵介绍

The double speed output motor pump has high and low pressure output, and the pressure flow can be automatically converted to speed up the rescue process; Using single pipe single interface connection mode can realize the pressure replacement tool ". The upper "type metal control valve block can not only control two tools to work at the same time, but also has the" double speed valve " technology, which can double the rescue efficiency of one tool.



Automatic conversion





#### Double Speed Valve Technology

倍速阀技术

The control valve switch makes the growth rate possible, in which either of the two connected devices can provide double flow by the control valve switch. When the control valve switch is pushed to one side, the oil supply to the other side of the device, that is, double the output flow to the directed side to double the operation speed.



Adopt high quality single connector imported from abroad, with locking function and dust-proof device; single joint and double output design, can connect two products and work at the same time, with double speed technology; concentric shaft single joint design, single joint can be With pressure plug and pull



#### Main Features

主要特点

- 01/ The motor pump has both high and low pressure pressure output, and the pressure flow can be automatically converted to speed up the rescue process.
- 02/ Single pipe and single joint connection mode can realize the replacement product with pressure
- 03/ "Upper" type metal control valve block, not only can control two products work at the same time, but also has "speed valve" technology, can double the rescue efficiency of one product;
- 04/The motor pump adopts advanced aviation hydraulic oil, which can be worked in -30~55 environment;
- 05/Compaction and small space; Light weight, mobile convenience, effectively reduce the physical consumption of rescue workers;
- **06**/Adopt high quality single connector imported from abroad, with locking function and dust-proof device; single joint and double output design, can connect two products and work at the same time, with double speed technology; concentric shaft single joint design, single joint can be. With pressure plug and pull

www.aolairescue.com



# PCDS-SX

# **Amphibious Hydraulic Breaking Tool Set Double-acting**



72Mpa Rated working pressure

Technical Parameter

技术参数

01/ Rated working pressure	72MPa
02/ Underwater working depth	110m
03/ Lithium battery capacity	14Ah
04/ Weight	18.9kg


3.0
3.0 (5Mpa) Low-pressure flow rate





### JQ-SX-B

#### Amphibious Hydraulic Cutter



#### Technical Parameter

#### 技术参数

01/ Rated working pressure	72MPa
02/ Opening distance	165mm
03/ Underwater working depth	110m
04/ Cutting capacity(Q235A)	Can cut 30mm round bar、16mm plate.
05/ Weight(kg)	13.3kg

CD-SX-B

Amphibious hydraulic jacking and spreading device



927

927mmSpreading distance

#### ■ Technical Parameter 技术参数

01/ Rated working pressure	72MPa
02/ First-stage jacking force	155.48kN
03/ Second-stage jacking force	70.79kN
04/ First-stage jacking length	687mm
05/ Second-stage jacking length	927mm
06/ Retracted length	487mm
07/ Jacking stroke	The jacking stroke of the first stage is 200 millimeters and the jacking stroke of the second stage is 240 millimeters.

KZ-SX-B



#### Technical Parameter

#### 技术参数

01/ Rated working pressure	72MPa
02/ Maximum spreading force	65.42kN
03/ Minimum spreading force	55.43kN
04/ Spreading distance	330mm

#### Introduction Of The Amphibious Tool Group

#### 水陆两用工具组介绍

The amphibious tool group was originally developed and produced to solve the practical difficulties faced by rescue organizations around the world. The amphibious demolition tools group break traditional hydraulic demolition tools can not be land and underwater dual-use work rescue imprisonment, the whole set of tools consists of underwater battery pump, underwater cutter, underwater spreader and underwater jacking device which can dive into the deep water area for shear, expansion and roof the rescue operation.







#### Main Features

#### 主要特点

- **01/** The main part is made of high strength alloy, with high strength and light weight
- 02/ All the seals are come from the original import, with better quality.
- **03/** Light weight, large force, high efficiency, simple operation.
- **04/** Equipped with a buoyancy device to ensure the relative buoyancy and flexibility of the tool



# ZJS(A-JYSJJ-SJJ) Tripod

• 01 =

The product material uses high strength aviation aluminum alloy material, high strength, light weight.

• 04 =

Its different lengths and stents enable the system to be applied in various environments.

The lock ring is treated by mechanical embossing to prevent hand slip.

03\_

The versatility of the system makes it an ideal system for the following

industries system, fire rescue and emergency services industry, construc-

tion industry, military field, irrigation industry, motor drive line industry,

communication industry, mining industry, film industry and mainte-

Simple and easy to use, including fixation, connection, supporting and locking.

#### Rescue Support Introduction

救援支架介绍

• 02-

Rescue support is a borderline hazardous environmental rescue system. Provide ultimate users a wide range configuration option. Complete multi-function bracket system includes: lifting rod, armrest bracket, A type frame, slippery wheel bracket type A frame, steering A type frame, tripod,the four-legged frame, bridge support. Through a hinge-like group installation method, add or remove the die head quick plug assembly can be very quickly assembled into different structures.

All aluminum alloy parts are treated at high temperature to increase strength

The form of the structure adapt to most of the harsh conditions of the emergency rescue, it can show a strong working ability in the cliff operating, deeping pit work industry and flat working environment. Match with rope and winch mechanism to maximize rescue benefits and increase stability.

### Technical Parameter

nance industry.

技术参数

# 01/ Contraction length 1623mm 02/ Spreading height 2940mm 03/ Rated load mass 180kg 04/ Breaking tensile force of steel wire rope 22KN 05/ Weight 40kg (include all parts)

#### Main Features

主要特点

- 01/ The product material uses high strength aviation aluminum alloy material, high strength, light weight.
- **02/** All aluminum alloy parts are treated at high temperature to increase strength and durability.
- 03/ Its different lengths and stents enable the system to be applied in various environments.
- 04/ The lock ring is treated by mechanical embossing to prevent hand slip.
- **05/** Simple and easy to use, including fixation, connection, supporting and locking.


AOLAI-RESCUE | 奥来产品 COMPANY PROFILE 企业简介

## **AIR LIFTING BAGS**

Main Features

tant, reinforcing role, long service life

主要特点



Small volume, thin thickness, large stroke. It can lift heavy objects in very narrow gaps

01/ The surface has no-slip convex points, which plays a fixed role of no-slip rubber

03/ Small volume, thin thickness, large stroke. It can lift heavy objects in very narrow gaps

04/ Copper intake nozzle, built-in thread and easy to connect the fast joint of the quick joint.

02/ Thickening layer. The material is wear-resistant and aging-resistant rubber, which plays a wear-resis-







Connection

#### www.aolairescue.com PAGE-047

### **Standard Configuration**



#### Introduction of the Square Air Lifting Bags

起重气垫套组介绍

Lifting air bags is a rescue aid lifting product powered by compressed gas, which can lift weights in extremely narrow bag. It has remarkable characteristics of thickness thin, large travel, short lifting time, strong adaptability.

#### **Technical Parameter**

Square lifting air bags		Size (cm)		Weight	Working pressure	Demand for gas	Max. lifting tonnage	Max. lifting height
Model /Specification	Length	Width	Height	kg	bar	L	Т	cm
QQD3-5/0.8(5T)	30	30	2.5	2.4	8	42	5.5	16
QQD5-10/0.8(10T)	38	38	2.5	4.2	8	86	10.1	21
QQD7-10/0.8(15T)	45	45	2.5	6	8	152	13.5	25
QQD10-15/0.8(20T)	55	55	2.5	8.5	8	296	21.6	30
QQD15-15/0.8(30T)	61	61	2.5	11.5	8	416	27.8	34
QQD23-20/0.8(45T)	78	78	2.7	19.1	8	921	45	42
QQD27-20/0.8(55T)	87	87	2.7	23.9	8	1305	55	47
QQD27-20/0.8(68T)	95	95	2.7	26.5	8	1408.1	65	53

# EHK-5B

### **Battery Hydraulic Rescue Backpack EHK-5B**



#### Brief Introduction

Main Features

01/ The main part is made of high strength alloy, high strength and light weight.

mobility and usability.

02/ All seals are imported from the original manufacturer and are of high quality.

03/ Light weight, great power, high efficiency, can be single-handed operation

04/ Comes standard with two backpacks that can be carried on the back or by hand. Excellent mobility and usability.

05/ One-handed operation mode, to achieve more flexible use of products in

06/ With the function of wireless remote control, the potentially dangerous operation can be realized. It can better protect the rescuer during potentially dangerous operations.

#### EHK-5B介绍

The Remote Control Battery Rescue Backpack EHK-5A1 set is composed of: electric pump, micro-door opener, micro-spreader, micro-cutter, Rebar cutter, crowbar and other products. It is characterized by light weight, great strength and high efficiency.

realized. It can better protect

the rescuer during potentially dangerous operations.

It is often used in demolition work, especially for concrete demolition. It is a single-tube, single-handed operation machine that can be operated by a single hand.

It is a miniature hydraulic rescue product with a single hose that can be operated manually.

### **DOOR OPENER**



#### Technical Parameter

技术参数

01/ Rated working pressure	50MPa
02/ Max. spreading force	63.58kN
03/ Spreading distance	260mm
04/ Closed length	460mm

### MICRO SPREADER



#### Technical Parameter

技术参数

01/ Rated working pressure	50MPa
02/ Max. spreading distance	90mm
03/ Spreading force	31.3kN

#### **MICRO CUTTER** 微型剪切器



#### Technical Parameter

技术参数

01/ Rated working pressure	50MPa
02/ Cutting capacity (treated steel)	Can cut 20mm round bar
03/ Opening distance	35mm

#### **BATTERY PUMP** 电动泵



#### Technical Parameter

技术参数

01/ Hydraulic oil tank capacity	1L
02/ Engine power	450W
03/ Chargeable Battery	24V、 5Ah
04/ Weight	14.28kg
05/ Operation type	Wired controller

#### www.aolairescue.com



# **BJK-A**

**Hand-operated Combi Tool** • 03-The tool adopts high strength, high toughness • 02imported steel, the sealing ring is imported, the quality Integrated design, no external is stable and reliable: power source, with cut, spread, • 01 pull and squeeze functions; High power, high efficiency, compact structure and easy maintenance; • 04-• 05-The body adopts high-strength 360° rotation handle to meet any Angle of aviation aluminum alloy, light weight, high strength, ceramic

surface more wear-resistant;

#### Brief Introduction

#### 便携式的剪扩器A介绍

The pump, fuel tank and tools are integrated together, the weight is only 10kg, and it has many functions such as spreading, cutting, squeezing and pulling. Lightweight, easy to carry, transport and use, No external power source and hose required, the portable hydraulic rescue combi tool can work independently. The assembly part for cutter and hand pump can be freely rotates 360° so it is always in the ideal working position.

Usually used in firefighting, earthquake rescue, traffic rescue and other emergency rescue scenarios.

#### Main Features

主要特点

- 01/ High power, high efficiency, compact structure and easy maintenance;
- 02/ Integrated design, no external power source, with cut, spread, pull and
- 03/ The tool adopts high strength, high toughness imported steel, the sealing ring is imported, the quality is stable and reliable;
- 04/ The body adopts high-strength aviation aluminum alloy, light weight, high strength, ceramic surface more wear-resistant;
- 05/360° rotation handle to meet any Angle of operation;

#### **Technical Parameter**

01/ Rated working pressure	63Мра
02/ Max. cutting force	392KN
03/ Spreading distance	≥160mm
04/ Spreading force	31.4~33.3KN
05/ Cutting capacity (Round bar)	10mm(Steel plate) ф20mm( round steel)
06/ Weight	10.2kg
07/ Applicable temperature	-30°C∼55°C
08/ Dimensions (L*W*H)	735*212*146mm



# FDMP-7

### **Door Breaking Kit (6)**

• 01 -

The main body is made of high-strength alloy, which is strong and lightweight. High strength and light weight.

• 02-

All seals are imported from Europe and the United States. The quality is better and the reliability is better.



• 03-

Powerful, efficient, and simple one-handed operation.
Simple, single-handed operation.

• 04-

Flexible use in small spaces.

#### Main Features

主要特点

- **01/** The main body is made of high-strength alloy, which is strong and lightweight. High strength and light weight.
- **02/** All seals are imported from Europe and the United States.The quality is better and the reliability is better
- 03/ Powerful, efficient, and simple one-handed operation. Simple, single-handed operation.
- 04/ Flexible use in small spaces.

#### FDMP-7 Multi-function axe



#### GYKZ-42/150-W Mini spreader



www.aolairescue.com PAGE-063

#### Brief Introduction

便携式防盗门破拆工具组介绍

The tool set is mainly used for breaking open roll-up curtains and metal burglary alarms, and includes:

hydraulic manual pumps, door openers, Mini spreader, Mini cutter, rebar cutter, and multi-function axes, etc., and single-hose, single-hand-operated, lightweight and miniaturized hydraulic rescue equipment.

#### ■ Technical Parameter

技术参数

01/ Weight	2.07kg
02/ Length	307mm

#### Technical Parameter

技术参数

01/ Spreading distance	150mm	
02/ Spreading force	48.5kN	
03/ Weight	3.25kg	

#### BS63/0.8-B Hand pump



#### Technical Parameter

技术参数

01/ Rated working pressure	72MPa
02/ Rated flow rate	0.83ml/per time
03/ Low pressure flow rate	7.5ml/ per time
04/ Hydraulic oil tank capacity	0.7L
05/ Max handle force	260N
06/ Weight	2.92kg
07/ Dimensions (LxWxH)	400*115*150mm

#### GYSD-63-14/28-A Rebar cutter



#### ■ Technical Parameter 技术参数

01/ Rated working pressure	72MPa
02/ Max opening distance	22mm
03/ Cutting capacity	Q235 Round bar φ18mm
04/ Weight	2.6kg
05/ Dimensions (L x W x H)	300*60*55mm

#### GYJQ-63-18/60 Mini cutter



#### Technical Parameter

技术参数

01/ Opening distance	62mm
02/ Cutting capacity	Q235 Round bar φ18mm
03/ Weight	2.91kg

#### GYKM-63-60/100-W Door opener



#### ■ Technical Parameter 技术参数

01/ Max. spreading distance on toe

180mm cylinder stroke is 100.0)

02/ Max. opening force on saddle

51.73kN

03/ Weigh

3.92kg

# CJS6000-B

### **Manual Breaking Tool Kit (8)**



The special design makes the operation force completely concentrated on the breaking point, in order to achieve the purpose of saving time and labor and high efficiency;

• 03\_

High strength steel forging, coated with anti-rust and anti-corrosion coating is easy to maintain

• 05-

It does not require a lot of swinging operation space, especially suitable for use when there are many people around or in the dark.



#### **Brief Introduction**

手动破拆工具组介绍

Aolai series manual breaking tools does not need power, are rescue tools carried carried by one person for manual operation, equipped with chisel, cutting, smashing, prying and other working methods of the working head. Especially suitable for the initial earthquake rescue work, can break wall buildings, floors, windows and doors of vehicles, locks, etc., in the case of other rescue equipment can not be deployed, can quickly rescue trapped people.

#### **Technical Parameter**

技术参数

01/ Distance between the impactor jack and the side	24.4mm	02/ Distance to the side of the jack of the working head	23.8mm	03/ Cutter claw length	465mm
04/ Length of nail puller claw	454mm	05/ Long and wide chisel length	462mm	06/ Long narrow chisel length	455mm
07/ Long pointed chisel length	460mm	08/ Short narrow chisel claw le	ngth 230mm	09/ Short pointed chisel length	228mm
10/ Total weight	18.72kg	10/ Hardness	506HBW5/750		

#### www.aolairescue.com

PAGE-065

### Standard Configuration



#### Main Features

主要特点

- 01/ The impact head is made of high-strength tool steel. The impact head is made of high-strength tool steel for strength, toughness and durability;
- 02/ The moving parts are equipped with protective cover, shear anti-splash, automatic reset manual steering valve, etc., to provide safety assurance for the operator;
- 03/ High strength steel forging, coated with anti-rust and anti-corrosion coating is easy to maintain
- 04/ The special design makes the operation force completely concentrated on the breaking point, in order to achieve the purpose of saving time and labor and high efficiency;
- 05/ It does not require a lot of swinging operation space, especially suitable for use when there are many people around or in the dark.





Light weight



Original



RXR-MC80BD

**Fire Robot** 

#### Main Features

主要特点

#### 01\_

The water cannon adopts electronically controlled fire water cannon with a flow rate of 80L/s.

02-

The electric chassis has a range of up to 8h and is equipped with a water cannon and a detector.

• 03-

The gas detection module integrates the camera, gas detector and pickup on the same lift-down head, providing the operator and decision maker with clear images and sound collection of the rescue scene, and also can

detect harmful gases such as flammable and explosive.

04-

The Fire Extinguishing Robot is a remote-controlled robot that can assist in fire rescue.

#### **Technical Parameter**

技术参数

01/ Working pressure (MPa)	0.8~1.2	07/ Working time (h)	2~8	12/ Brake mode	Electromagnetic brak
02/ Range (m)	88	08/ Speed (km/h)	5.8	13/ Protection level	IP 67
03/ Flow rate (L/s)	80	09/ Barrier height (mm)	200	14/ Battery	48、120
04/ Horizontal movement angle (°)	-90~+90	10/ Gradeability	Traverse side slopes 45°; Ascend slopes Side slope 35°	15/ Weight (kg)	560
05/ Vertical movement angle (°)	-15~+90	11/ Remote control dist	ance (m) 1200	16/ Dimensions (mm) (L*1	<b>W*H)</b> 1370x840x1220
06/ Water supply interface (mm)	80x2				

#### Strong Fire Extinguishing Ability

灭火能力强

Adopt the Amiron electronic control fire water cannons the flow can up to 80L/s, have a better fire fighting ability. Equipped with Amiron 3482 water cannon, the robot have straight stream and fog two modes: straight stream mode for solid fire extinguish. Fog mode can also be used for cooling and fire rescue.

Self-defense water curtain protection can make sure that the robot work in high temperature environment.

#### Strong Investigative Ability

侦检能力强

The gas detection module integrates the camera, gas detector and pickup on the same lift-down head, providing the operator and decision maker with clear images and sound collection of the rescue scene, and also can detect harmful gases such as flammable and explosive. The gas detection module is loaded on a platform with camera, microphone and detector, can provide the ph—otos,voice and the data of dangerous gas to rescuers. The detector can analysis six kinds of different dange- rous gas,then rescuers can choose the best way for the rescue operation. Besides, it can also detect and track the heat source through the equipped hot eye detec- tion platform.





## AOLAI-RESCUE

# **AL18**

## HYDRAULIC POWER STATION

#### Product Features

产品特点

04.

One-button on/off design, full range of electronic control design, one-button on/off of hydraulic oil, easy and fast operation



• 02.

Compact structure, light weight, easy to transport

03.

The new shock-absorbing design cuts off the high-frequency vibration of the gasoline engine at the source, greatly reducing the risk of cracking of the fuel tank and frame.

#### 01.

Stable and reliable performance, imported engine, large capacity hydraulic oil radiator

#### Product Introduction

AL18 简介

The standard hydraulic power station provides a convenient and reliable power source for various hydraulic tools, and is suitable for work scenarios such as road repair and road construction.







#### **Technical Parameter**

<b>01</b> / Gas	oline Engine	18HP Briggs & Stratton 18HP
<b>02</b> / Maxi	mum hydraulic system լ	oressure 16Mpa
<b>03</b> / Hyd	raulic flow	2*20/1*40lpm
<b>04</b> / Dim	ensions	980*560*800mm
<b>05</b> / Bare	Metal Weight	140kg
<b>06</b> / Hyd	raulic oil tank capacity	/ 18L
<b>07</b> / Fuel	tank capacity	20L
<b>08</b> / Star	ting method	Electric
<b>09</b> / Oil c	ircuit and control method	d Electronic Control



# **AL13**

#### SINGLE CIRCUIT HYDRAULIC **POWER STATION**

### Product Features 产品特点

• 03.

One-button switching of hydraulic oil, easy and quick operation



01.

02.

Compact structure, light weight, easy to transport

> Stable and reliable performance, high-reliability engine, large-capacity hydraulic oil radiator

#### Product Introduction AL13 简介

A small, portable, low-medium pressure hydraulic power source. It provides a convenient and reliable power source for various hydraulic tools and is suitable for work scenarios such as road repair, road construction, and municipal maintenance.

#### Technical Parameter

01/ Gasoline Engine	13HP
02/ Maximum hydraulic system	pressure 16Mpa
03/ Hydraulic flow	18-30lpm(Adjustable)
<b>04/</b> Starting method	Electric start/pull rope start
<b>05</b> / Oil circuit control method	Manual Control
<b>06</b> / Number of oil return lines	one
07/ Noise level	90db

## **AL27-TWIN**

#### **DUAL CIRCUIT HYDRAULIC POWER STATION**



01.

High and low voltage integrated, dual interface output, one machine for multiple uses

02.

Compatible with concrete demolition tools and metal demolition tools

05.

Shock-absorbing design cuts off the high-frequency vibration of the gasoline engine at the source, greatly reducing the risk of cracking of the fuel tank and frame.

#### **Product Introduction** AL27-TWIN 简介

• 04.

The dual-circuit hydraulic power station has the function of displaying pressure and working time. It is convenient for real-time monitoring of pressure conditions and is also conducive to rapid troubleshooting and handling of faults. Equipped with a microcomputer controller, it adjusts the engine output power in real time according to the load conditions to achieve the best fuel utilization



#### **Technical Parameter**


01/ Output Interface	High voltage dual interface output
<b>02</b> / Hydraulic power take-off	low voltage dual interface output
03/ Engine power	27hp
<b>04/</b> Low pressure output pressure	ure (bar) 165bar
<b>05</b> / High pressure output press	sure (bar) 638bar
<b>06</b> / Low pressure maximum floo	w output (lpm) 60.3lpm
<b>07</b> / High pressure minimum flow	w output (lpm) 2.4lpm
08/ Starting method	Electric start



▲ AOLAI-RESCUE | 为人类与自然的和谐服务 COMPANY PROFILE | 混凝土工具

# ALHB-20

#### **HEAVY HYDRAULIC BREAKER**



concrete, rock, asphalt, frozen soil, brick wall, etc. It has a compact structure and a wide

21.8 KG

30.1 lpm 1515bpm

165bar

6.5m/s<sup>2</sup>

range of applications. Although it is light in weight, it can complete various tough

crushing tasks. The equipment is an integral or shock-absorbing handle, and the

Technical Parameter

技术参数

01/ Weight **02**/ Flow

03/ Impact rate

04/ Work Pressure

05/ Vibration intensity (m/s²)










PAGE-012

# HYDRAULIC DISC SAW





#### **Product Introduction**

液压圆盘锯简介

Hydraulic circular saw is a commonly used hydraulic power cutting tool. It can be used to cut concrete, masonry, pipes, structural steel beams and guardrails with different saw blades. This equipment has the advantages of high efficiency, low noise, high reliability, small size and light weight, and is very suitable for various engineering and emergency



#### **Technical Parameter**

01/ Saw blade diameter	355mm
02/ Maximum cutting depth	132mm
03/ Maximum speed of return plate	4630rpm
<b>04</b> / Workflow	20~40L/min(Adjustable)
<b>05</b> / Maximum working pressure	165bar
<b>06</b> / Vibration acceleration (vibration le	vel) 2.2m/s
07/ Weight	12.1kg

# HYDRAULIC ROCK DRILL ALHB-10

### **Product Features** 产品特点 01. Ergonomic design, more comfortable to operate 03. Built-in integrated air compressor with rotary and impact working • 02. modes Suitable for demolition work indoors or in narrow spaces

#### **Product Introduction** 液压岩石钻简介

It is widely used in the demolition and partial reconstruction of various reinforced concrete foundations (such as steel furnaces, various heavy equipment, tower cranes, dams, hydraulic structures of hydropower stations, bridge piers, etc.); demolition of reinforced concrete floors/walls; demolition of indoor or narrow room concrete structures.

#### **Technical Parameter** 技术参数

01/ Working Mode Rotation, impact mode **02/** Slag cleaning mode Built-in integrated air compressor 03/ Impact frequency (times/minute) 1520 /min 04/ Flow rate (lpm) 40lpm **05**/ Maximum working pressure (bar) 160bar **06**/ Maximum drilling diameter (mm) 55mm 07/ Maximum drilling depth (m) 3.006m 08/ Weight(kg) 19.2kg

#### LIGHT HYDRAULIC BREAKER

#### Product Features

产品特点



















#### Product Introduction

ALHB-10 简介

Light hydraulic breaker is specially designed and manufactured for crushing concrete, rock, asphalt, frozen soil, brick wall, etc. It is widely used in highway, municipal, gas, highway, electric power, telecommunications, railway, fire protection and construction industries. This product is an integral shock-absorbing handle with compact structure and light weight, and the operation mode is vertical downward operation.

#### Technical Parameter

技术参数


04/		
01/	Flow	20lpm
02/	Impact frequency (times/minute)	2120/min
03/	Vibration intensity	9.6m/s²
04/	Weight	9.6kg

www.aolairescue.com

Ergonomic

# ALDS-3

#### **HYDRAULIC CHAIN SAW**



切割深

效率高

结构紧凑

功率高





www.aolairescue.com PAGE-016

#### Product Introduction

ALDS-38 简介

Hydraulic diamond chain saw can be used for cutting rock, concrete, etc., with a deeper cutting depth. Light weight, high efficiency, compact structure, high power, long life and easy mainte-

#### Technical Parameter

01/ Weight	9.7KG
02/ Cutting Depth	382mm
03/ Chain plate size	504mm
<b>04/</b> Working pressure	174bar
<b>05</b> / Flow	31.8lpm

entering the hydraulic system

# ALRS-40

#### **HYDRAULIC ANNULAR SAW**



Ergonomic handle and machine

03.



#### **Product Introduction**

ALRS-40 简介

Hydraulic circular saw is the perfect tool for cutting mixed meal, brick wall, asphalt, etc. The equipment is small in size, light in weight, and deep in cutting. The cutting depth of the hydraulic circular saw is more than 1.5 times that of the traditional disk saw, and this kind of product has been widely pushed by emergency rescue personnel, and the application field is constantly expanding.



#### **Technical Parameter**

01/ Bare weight	10.2kg
<b>02</b> / Flow	20-40 lpm
03/ Maximum working pressure	163bar
04/ Maximum cutting depth	300mm
05/ Saw blade diameter	400mm
<b>06</b> / Rotation speed	1750-2350 rpm
<b>07</b> / Vibration intensity	< 2.5m/s²

# ALRP-90

### HANDHELD CONCRETE

#### **SPLITTER**

### Product Features 产品特点



#### Product Introduction ALRP-90 简介

The concrete handheld hydraulic splitter is a hydraulic driven rock splitting equipment. The product uses high pressure hydraulic oil as the power source, cleverly applies the oblique wedge doubling principle, the splitting force of the rock reaches hundreds of tons, or even thousands of tons, and the splitter can easily split the boulder in a few seconds, so that the hard ore is separated from the mountain.

#### www.aolairescue.com

PAGE-018


#### Technical Parameter 技术参数

01/ Aperture (mm)	45-48mm
<b>02</b> /Splitting force (t)	375.2t
03/ Max hole depth (mm)	608mm
04/ Crack width (mm)	72mm
05/ Split length (mm)	1035mm
06/ Length of wedge (mm)	245mm
<b>07</b> / Weight (kg)	29kg

# ALCB-74

### **DOUBLE-BLADE INTERNAL COMBUSTION CUTTING SAW**

### Product Features 产品特点



Low noise, low vibration, comfortable operation, no pollution, safety and environmental protection

The large distance between the handles allows the operator to operate in a comfortable position and reduces tension

#### Product Introduction

ALCB-74 简介

Double-blade internal combustion cutting saw engine does not need an external power source to operate strong power, in the industry, it can complete a very difficult to complete the work, small size, light weight and easy to carry, double saw blade cutting saw effect is higher, there are traditional cutting saw can not replace the advantages.



#### **Technical Parameter**

01/	Engine	Air cooling 2 stroke
02/	power (kw)	3.7kw
03/	Maximum cutting depth (mm)	402mm
04/	Saw blade maximum speed (rpm	) 5924rp
05/	Displacement (cc)	74cc
06/	Ultimate peripheral speed (m/s)	80.6 m/s
07/	Weight (kg)	11.6kg

▲ AOLAI-RESCUE | 为人类与自然的和谐服务 COMPANY PROFILE | 混凝土工具

# **SLURRY PUMP**

#### **SLURRY PUMP**

### Product Features 产品特点



#### Product Introduction

渣浆泵简介

Using cast aluminum shell, light weight, high efficiency, compact structure, light weight, high work, long life, easy to maintain, the world's top sealing ring brand with patent seal structure, high reliability, long service life, easy

#### Technical Parameter 技术参数

<b>01</b> / Material	All-metal cast aluminu	um shell
<b>02</b> / Flow (lpm)	20-30(Adj	ustable)
03/ Maximum working pre	essure (bar)	239bar
04/ Maximum working pre	essure (bar) 106.3	3 (m / h)
05/ Head of delivery (m)		25.6m
06/ Suctable diameter of	solid particles (mm)	70(mm)
07/ Weight		10.9kg

Cast aluminum, light and durable, long service life

# **ZDSP-4515**

**HYDRAULIC** SUBMERSIBLE PUMP



#### **Product Introduction** ZDSP-4515 简介

Large flow portable hydraulic submersible pump is widely used in urban flood control and drainage, emergency rescue and relief, field Engineering construction, subway construction and water supply and drainage occasions in places without three-phase power supply.



#### **Technical Parameter**

技术参数

01/	Hydrauli	ic flow rate is			38L/ min
02/	Displace	ement			405.1 m <sup>3</sup> /h
03/	Pump	304 stainless s	steel material, corrosic	n resistance, we	ar resistance
04/	Head of	delivery (m)	4.4 m (displace	ment not less th	an 390 m³/ h)
05/	Working	medium and t	emperature range	≤70°C Non-co	orrosive liquid
	(	such asclean wa	ater and sewage (parti	culate matter dia	ameter 25mm
06/	Working	environment a	and working	-15~+50℃ in	door and field
	tempera	ture			PAGE-02

www.aolairescue.com